

STANDARD ACCESSORIES

ARCTIC-LOCK[®] COUPLER

- ▶ Designed for cold temperatures
- ▶ Increased impact strength reduces the risk of cracking or shattering under installation force
- ▶ Can withstand at least 35% higher impact than standard Clear-Lock couplers, or 4.7 Jauls impact at -18C
- ▶ Ideal for pull boxes, vaults or other limited access areas
- ▶ Non-metallic construction provides excellent corrosion resistance in buried or encased applications and also has desirable dielectric properties
- ▶ Simple, one person 'push-on' assembly lowers installation costs
- ▶ Self-locking ring design assembles in seconds and is re-enterable
- ▶ High strength molded plastic body is ideal for buried duct applications
- ▶ Pre-lubricated O-ring is water-tight and air-tight
- ▶ Suitable for both cable pulling & jetting applications



ORDER REFERENCE

DESCRIPTION	NOM OD	DUCT OD WORKING RANGE	LENGTH (IN)	PULL OUT STRENGTH (LBS)	MAX PRESSURE (PSI)	CARTON QTY	DURA-LINE PART #
3/4" ARCTIC-LOCK Coupler	1.050"	1.040" - 1.060"	3"	270	250	144	20094317
1" ARCTIC-LOCK Coupler	1.315"	1.305" - 1.325"	2.6"	400	250	50	20094318
1 1/4" ARCTIC-LOCK Coupler	1.660"	1.650" - 1.670"	5"	650	250	50	20094319
1 1/2" ARCTIC-LOCK Coupler	1.900"	1.890" - 1.910"	5.5"	850	250	25	20094320
2" ARCTIC-LOCK Coupler	2.375"	2.365" - 2.385"	7"	1,350	250	15	20094321