

STANDARD ACCESSORIES

CONDUIT CONNECT

Introducing Dura-Line's latest innovation in conduit coupling

- ▶ Specifically designed for use in all kinds of duct bank installations
- ▶ Ideal for joining lengths of HDPE Sticks but can also be used with continuous length, reeled products.
- ▶ Air- and water-tight with a pre-lubricated gasket for easy installation
- ▶ High strength HDPE body is ideal for buried duct applications
- ▶ UV resistant
- ▶ Superior pull-out strength
- ▶ Specialized for use by electrical installers requiring ETL/UL listing
- ▶ Patent pending
- ▶ Additional sizes coming soon



4" AND 6" ETL LISTED TO

- UL514B
- CSA STD C22.2 18.3-04

3" listing available soon

ORDER REFERENCE

CONDUIT CONNECT COUPLERS						
DESCRIPTION		NOM OD	DUCT OD WORKING RANGE (IN)	HEIGHT (IN)	PACKAGING	PART #
3" Conduit Connect		3.500"	3.480" - 3.520"	8.25"	Each	20097517
4" Conduit Connect		4.500"	4.480" - 4.520"	10.00"	Each	20096550
6" Conduit Connect		6.625"	6.605" - 6.645"	13.00"	Each	20096882



An Orbia Connectivity Solutions business.

+1 800 847 7661
WWW.DURALINE.COM

TL9000



DL.CONDUIT-CONNECT-9.25 US