STANDARD ACCESSORIES

CONDUITCONNECT®



Introducing Dura-Line's latest innovation in conduit coupling

The latest in Dura-Line's coupler collection, the ConduitConnect is specifically designed to meet the rigorous demands of duct bank installations and your go-to solution for a wide range of electrical and telecom applications. Whether you're working with HDPE or PVC sticks or continuous length reeled products, this coupler delivers a secure, reliable connection every time.

FEATURES

- Ideal for joining lengths of HDPE or PVC Sticks but can also be used with continuous length, reeled products.
- Air- and water-tight with a pre-lubricated gasket for easy installation
- High strength HDPE body is ideal for buried duct applications
- UV resistant
- Superior pull-out strength
- Specialized for use by electrical installers requiring ETL certification

- 4" and 6" ETL Listed / Conforms to UL Standard 514B
- 4" and 6" ETL Listed / Certified to CSA Std. C22.2 18.3-04
- Additional listings available soon

ORDER REFERENCE

CONDUITCONNECT COUPLERS							
DESCRIPTION	NOM OD	DUCT OD WORKING RANGE (IN)	PULL OUT STRENGTH (LB)	HEIGHT (IN)	PACKAGING	CASE	PART #
2" ConduitConnect	2.375"	2.355" - 2.395"	800	7.53"	Case	10	20097763
2 1/2" ConduitConnect	2.875"	2.855" - 2.895"	1,000	7.56"	Case	6	20098779
3" ConduitConnect	3.500"	3.480" - 3.520"	1,000	8.25"	Case	6	20097832
4" ConduitConnect	4.500"	4.480" - 4.520"	1,000	10.00"	Case	4	20098052
4" EXT ConduitConnect	4.500"	4.480" - 4.520"	1,000	13.20"	Case	4	20098053
5" ConduitConnect	5.563"	5.543" - 5.583"	1,000	14.70"	Case	2	20098346
6" ConduitConnect	6.625"	6.605" - 6.645"	1,000	13.00"	Case	2	20098054
6" EXT ConduitConnect	6.625"	6.605" - 6.645"	1,000	14.25"	Case	2	20098055
8" ConduitConnect	8.625"	8.605" - 8.645"	1,000	16.00"	Case	1	20098325