


STANDARD CORRUGATED

- Manufactured from flexible HDPE
- Rugged corrugated design is flexible and light weight, yet provides excellent crush resistance
- Outstanding long term cable protection from shifting ground, rock and root impingement
- Provides a permanent pathway, simplifies future cable repairs or replacement
- Factory pre-installed Bull-Line™ Pull Tape with EVEN-LOAD™, ensures extra slack at any access point throughout the reel. Available 500 lb–6,000 lb tensile strength or locatable. Comes standard on 2"; is available for 1"-1 1/2"



INSTALLATION TYPES

Existing Conduit
Short Runs

SIZES RANGE

1"	1 1/2"
1 1/4"	2"

STANDARD COLORS


 custom colors available

FEATURES

STANDARD

MATERIAL Manufactured from flexible HDPE (High Density Polyethylene)

SPECIFICATIONS All Corrugated conduit dimensions meet or exceed ASTM D-3350

CONDUIT MARKINGS Permanent marking along conduit includes: material, relevant standards, production info, and sequential feet or meter markings. Custom options available.

OPTIONS


PRE-INSTALLED TAPE Factory pre-installed Bull-Line™ Pull Tape with EVEN-LOAD™ ensures extra slack at any access point throughout the reel. Available 500lb–6,000lb tensile strength or locatable.

UV PROTECTANT UV protectant available for above ground applications



+1 800 847 7661
WWW.DURALINE.COM





CORRUGATED TECHNICAL SPECIFICATIONS

NOMINAL SIZE	NOMINAL OD (IN)	ID REF (IN)	MIN WALL THICK (IN)	BRITTLENESS TEMP	WEIGHT (#/FT)
1"	1.385	1.085	0.045	-60° C	0.042
1 1/4"	1.570	1.440	0.045	-60° C	0.059
1 1/2"	1.824	1.670	0.055	-60° C	0.063
2"	2.490	2.045	0.020	-60° C	0.097

Note: All sizes meet UL 2024 four inch bend radius standard.