

MICROTECHNOLOGY

FUTUREPATH HYBRID 9-WAY

- FuturePath configuration mixing two popular MicroDuct sizes
- A perfect choice for customers who need to place two different micro cables at the same time, or would like to plan for future possibilities
- Multiple pathways for one installation cost, allows flexibility and future growth
- No special tools or equipment needed; installation uses the same as traditional conduit or innerduct

INSTALLATION TYPES

Plow
Trench
MicroTrench

Directional Bore
Tray

STANDARD COLORS

■ Oversheath ■ ■ ■ ■ ■ ■ ■ ■ ■ MicroDucts

MicroDucts: (1) Blue, (2) Blue, (3) Orange, (4) Green, (5) Brown, (6) Grey, (7) White, (8) Red (9) Black



CONFIGURATIONS

22/16mm MicroDuct (1) + 12.7/10mm MicroDucts (8)

FEATURES

STANDARD

SPECIFICATIONS/DETAILS FuturePath configuration consisting of two or more different sizes of conduit and or MicroDucts. Manufactured from flexible HDPE (High Density Polyethylene).

FILL RATIO Choose the correct MicroDuct size based on the Outer Diameter (OD) of desired MicroCable. Dura-Line recommends a fill ratio of 50% to 75% for optimal cable placement performance. Several factors impact jetting distance including the condition of route, bends, and equipment.

CONDUIT MARKINGS Permanent marking along FuturePath includes: material, relevant standards, production info, and sequential feet or meter markings. Custom options available.

CO-EXTRUDED LINING SILICORE® ULF (Ultra-Low Friction) is co-extruded inside the HDPE wall creating a slick, permanent, interior lining. SILICORE® ULF exhibits no loss in performance over time or in extreme temperature conditions.

INTERNAL RIBS Standard on MicroDucts

LOCATE WIRE Available with or without a 20 AWG insulated copper wire


RIP CORDS For easy opening of the oversheath



+1 800 847 7661
WWW.DURALINE.COM



FUTUREPATH HYBRID 9-WAY TECHNICAL SPECIFICATIONS




DUCT TYPES	MAX OD (IN)	HEIGHT (IN)	WIDTH (IN)	OVERSHEATH (IN)	WEIGHT (LB/FT)	BEND RADIUS SUP (IN)	BEND RADIUS UNSUP (IN)	SWPS (LB)
22/16mm + 12.7/10mm	1.98	1.98	1.98	0.070	0.528	20	40	2,811

† Safe working pull strength is calculated at 80% of tensile or breaking strength


* Unsupported Bend Radius guidelines should be followed during the installation process. The Supported Bend Radius are post-installation measurements.

MICRODUCT A TECHNICAL SPECIFICATIONS



MICRODUCT SIZE	OD (MM/IN)	MIN ID (MM/IN)
22/16mm	22/0.87	15.4/0.61

MICRODUCT B TECHNICAL SPECIFICATIONS



MICRODUCT SIZE	OD (MM/IN)	MIN ID (MM/IN)
12.7/10mm	12.7/0.50	9.8/0.39