CORRUGATED PLENUM

- Plenum listed to UL Standards 2024 (CSA FT-6), ideally suited for plenum applications
- Flexible, lightweight and easier to install than metal conduit
- Designed to protect existing cables and facilitate future cable installation or replacement
- When tested to UL2024/UL910 (CSA FT-6), Dura-Line's Corrugated Plenum is low-smoke producing and fire resistant as defined by the National Fire Protection Association when rating cables as suitable for use in ducts, plenum spaces

INSTALLATION TYPES

Interior

SIZE RANGE AVAILABLE

1 1/4"

1 1/2"



STANDARD

MATERIAL Corrugated Plenum is made from fire retardant materials which are fully ETL approved for Plenum applications per UL-2024/UL-910

SPECIFICATIONS ETL LISTED to UL-2024/UL-910 & CSA FT-6

CONDUIT MARKINGS Permanent marking along conduit includes: material, relevant standards, production info, and sequential feet or meter markings. Custom options available.

OPTIONS

PREINSTALLED TAPE Factory pre-installed Bull-Line™ Pull Tape with EVEN-LOAD™ ensures extra slack at any access point throughout the reel. Available 500lb–6,000lb tensile strength or locatable.

CORRUGATED PLENUM TECHNICAL SPECIFICATIONS

SIZE	NOMINAL OD (IN)	OD TOLERANCE +/-	AVG ID	WEIGHT (LB/FT)
1"	1.385	0.020	1.165	0.125
1 1/4"	1.570	0.020	1.350	0.130
1 1/2"	1.824	0.020	1.600	0.149





