

STANDARD ACCESSORIES

SHUR-LOCK II COUPLER

- ▶ Designed for coupling HDPE & PVC conduit
- ▶ Can also be used to couple dissimilar conduits such as HDPE to PVC, threaded or non-threaded metal conduit, or fiberglass (FRP) conduit
- ▶ Stainless steel band clamps (hand tightened using a 5/16" nut driver) and locking ring
- ▶ Pre-lubricated O-ring forms an air-tight seal to withstand 125 PSI
- ▶ One person installation; re-enterable, no special tools required
- ▶ Air- and water-tight
- ▶ No ID reduction
- ▶ UV resistant
- ▶ Excellent pull-out strength on HDPE, PVC, FRP and steel
- ▶ No-Stop version available for confined areas or repairs (*NS)
- ▶ Specialized for use by electrical installers requiring ETL/UL listing
- ▶ Listed to UL STD 514B and ETL Listed to CSA STD C22.2 18.3-04

NOTE: Certain sizes ETL-listed for use with HDPE and PVC for underground and concrete encased applications only! Not for use with PVC in above-ground applications. Not premise (indoor) rated.



AVAILABLE IN

- ▶ Classic
- ▶ No-Stop (NS)
- ▶ Transition

ORDER REFERENCE

Classic Shur-Lock II Couplers								
DESCRIPTION		NOM OD (IN)	DUCT OD WORKING RANGE (IN)	PULL-OUT STRENGTH (LBS)	HEIGHT (IN)	PACKAGING	CASE QTY	PART #
1" Shur-Lock II		1.315"	1.295" - 1.335"	600	5.70	Case	10	20000118
1 1/4" Shur-Lock II		1.660"	1.640" - 1.680"	700	5.70	Case	10	20000120
1 1/4" HYB Shur-Lock II		1.590"	1.570" - 1.610"	700	5.70	Case	10	20000121
1 1/2" Shur-Lock II		1.900"	1.880" - 1.920"	700	5.70	Case	10	20000122
2" Shur-Lock II		2.375"	2.355" - 2.395"	700	5.70	Case	10	20000123
2" EXT Shur-Lock II		2.375"	2.355" - 2.395"	700	8.25	Case	10	20000264
2 1/2" Shur-Lock II		2.875"	2.855" - 2.895"	1,000	9.25	Case	6	20000172
3" Shur-Lock II		3.500"	3.480" - 3.520"	1,000	10.75	Case	6	20000173
4" Shur-Lock II		4.500"	4.480" - 4.520"	1,000	12.00	Case	4	20000245
5" Shur-Lock II		5.563"	5.543" - 5.583"	1,000	14.25	Case	2	20000254
6" Shur-Lock II		6.625"	6.605" - 6.645"	1,000	14.25	Case	2	20000256



Please specify if ETL listing is required



An Orbia Connectivity Solutions business.

+1 800 847 7661
WWW.DURALINE.COM

TL9000



DL.SHURLOCK-7.25 US

ORDER REFERENCE

No-Stop Shur-Lock II Couplers

Center stop is removed to allow the coupler to be pulled back over the end of the duct for limited clearance installations.

DESCRIPTION		NOM OD (IN)	DUCT OD WORKING RANGE (IN)	PULL-OUT STRENGTH (LBS)	HEIGHT (IN)	PACKAGING	CASE QTY	PART #
1" NS Shur-Lock II		1.315"	1.295" - 1.335"	600	5.70	Case	10	20002340
1 1/4" NS Shur-Lock II		1.660"	1.640" - 1.680"	700	5.70	Case	10	20000236
1 1/2" NS Shur-Lock II		1.900"	1.570" - 1.610"	700	5.70	Case	10	20002341
2" NS Shur-Lock II		2.375"	2.355" - 2.395"	700	5.70	Case	10	20000237
2 1/2" NS Shur-Lock II		2.875"	2.855" - 2.895"	1,000	9.25	Case	6	20000238
3" NS Shur-Lock II		3.500"	3.480" - 3.520"	1,000	10.75	Case	6	20000239
4" NS Shur-Lock II		4.500"	4.480" - 4.520"	1,000	12.00	Case	4	20000260
5" NS Shur-Lock II		5.563"	5.543" - 5.583"	1,000	14.25	Case	2	20001531
6" NS Shur-Lock II		6.625"	6.605" - 6.645"	1,000	14.25	Case	2	20000261

Transition Shur-Lock II Couplers

DESCRIPTION		NOM OD (IN)	DUCT OD WORKING RANGE (IN)	PULL-OUT STRENGTH (LBS)	HEIGHT (IN)	PACKAGING	CASE QTY	PART #
1" - 1 1/4" Transition Shur-Lock II		1.315" / 1.660"	1.295" - 1.335" / 1.640" - 1.680"	600	5.70	Case	10	20096421
1 1/4" - 1 1/2" Transition Shur-Lock II		1.660" / 1.900"	1.640" - 1.680" / 1.880" - 1.920"	700	5.70	Case	10	20097278
1 1/4" - 2" Transition Shur-Lock II		1.660" / 2.375"	1.640" - 1.680" / 2.355" - 2.395"	700	5.70	Case	10	20097282
1 1/2" - 2" Transition Shur-Lock II		1.900" / 2.375"	1.880" - 1.920" / 2.355" - 2.395"	700	5.70	Case	10	20097281

Recommended Accessory: Shur-Lock Spreader Tool

Used to spread the tabs of large OD Shur-Locks for easier installation.

DESCRIPTION	PACKAGING	PART #
3" Shur-Lock Spreader Tool	Each	20095364
4" Shur-Lock Spreader Tool	Each	20095365
6" Shur-Lock Spreader Tool	Each	20095366

