

STANDARD ACCESSORIES

PUSH-LOCK COUPLER

- Compact profile is well suited for use in pull boxes, vaults, or other limited-access areas such as narrow trenches
- Non-metallic construction provides excellent corrosion resistance in buried or encased applications and also has desirable dielectric properties
- Non-transparent and contains UV inhibitors, but is not recommend for aerial applications
- Simple, one person 'push-on' assembly lowers installation costs
- Self-locking ring design assembles in seconds and is re-enterable
- High-strength molded plastic body ideal for buried duct applications
- Pre-lubricated O-ring is water and air tight suitable for both cable pulling & jetting applications
- Installation is fast and easy; no heat or tools are needed; simply push the duct ends into the coupler for a locked and air-sealed assembly



DESCRIPTION	NOM OD	DUCT OD WORKING RANGE	COLOR	LENGTH	TENSILE PULLOUT MIN-MAX (LBS)	MAX PRESSURE PSI	CARTON QTY	PART #
0.50" Push-Lock	0.840"	0.840"	White/Clear	3.5"	325	160	25	20003137
0.75" Push-Lock	1.050"	1.050"	Orange	3.5"	580	230	144	20001491
1.00" Push-Lock	1.315"	1.305"-1.325"	Orange	3.5"	600-800	250	50	20001844
1.25" Push-Lock	1.660"	1.650"-1.670"	Orange	5"	700-900	250	50	20001845
1.50" Push-Lock	1.900"	1.890"-1.910"	Orange	5.5"	800-1000	250	25	20001846
2.00" Push-Lock	2.375"	2.365"-2.385"	Orange	7.5"	2000-2400	250	15	20001847