

STANDARD ACCESSORIES

SPLIT-LOCK+ COUPLER

- Split coupler produced from a glass fiber reinforced nylon resin
- Heat and UV stabilized, offers excellent impact strength
- Fungus and chemical resistant
- Air and water tight
- No I.D. reduction
- Reusable and ideal for temporarily coupling conduits, particularly at slack-loop locations, and also for air-assisted jetting applications; can install with cable inside
- Easily assembled using a 7/16" nut driver, no special tools required
- Not recommended for plow chute
- Meets UL 514B pullout requirements
- ETL listed to UL STD 514B and CSA STD C22.2 18.3
- Made in the USA



DESCRIPTION	PACKAGING (CS)	SHIP WEIGHT (LBS)	PART NUMBER
Split-Lock + Coupler 1.00" SDR 	10	5.5	20003907
Split-Lock + Coupler 1.25" SDR 	10	5.5	20003908
Split-Lock + Coupler 1.50" SDR 	10	6	20003909
Split-Lock + Coupler 2.00" SDR 	10	6	20003910

RECOMMENDED ACCESSORY: PALM RATCHET

Used with Shur-Lock II and Split-Lock couplers.

DESCRIPTION	PACKAGING	SHIP WEIGHT (LBS)	PART #
Palm Ratchet with 5/16" and 7/16" Sockets	each	1	20002747



+1 800 847 7661
WWW.DURALINE.COM

