

STANDARD ACCESSORIES

COMPRESSION COUPLER



- Used to join and seal length of HDPE and PVC duct with a water-tight connection
- Internal double compression seal is created as the end caps are tightened
- Assorted sizes
- No special tools required
- Bulky
- Not recommended for cable blowing or plow chute applications
- Limited pull-out strength
- NOTE: PVC compression couplers are not recommended for high-pressure air or gas lines, or applications requiring high pull-off resistance.

DESCRIPTION	PACKAGING	SHIP WEIGHT (LBS)	PART #
13mm CATV w/o O-RINGS Fits 0.625" OD Duct	each	0.1	20001911
1/2" Fits 0.840" OD Duct	each	0.1	20001835
3/4" Fits 1.05" OD Duct	each	0.2	20001836
1" Fits 1.315" OD Duct	each	0.45	20001956
1-1/4" Fits 1.660" OD Duct	each	0.55	20001837
1-1/2" Fits 1.900" OD Duct	each	0.75	20002076
2" Fits 2.375" OD Duct	each	1.0	20001838
2-1/2" Fits 2.875" OD Duct	each	2.2	20001839
3" Fits 3.500" OD Duct	each	3.0	20003072
4" Fits 4.500" OD Duct	each	5.2	20001840
Adapter 1-1/4" Male Threaded Fits 1.660 OD Duct	each	0.35	20001912
Adapter 2" Male Threaded Fits 2.375 OD Duct	each	0.6	20003055



+1 800 847 7661
WWW.DURALINE.COM

