

STANDARD ACCESSORIES

HYDRACLEAN® C-200

- ▶ Effective solvent-based multipurpose cleaner and degreaser for electrical cable insulation, fiber optic cable constructions, metal, electrical and mechanical parts
- ▶ Does not contain ozone-depleting solvents or CFC's
- ▶ Excellent dielectric properties
- ▶ Complete evaporation – leaves no conducting residue
- ▶ Safe to work with – does not contain any known or suspected carcinogens
- ▶ No adverse effects on high and low density polyethylene, XLPE polyvinyl chloride, EPR or semi-conducting jackets.
- ▶ Mild odor, pleasant to work with – does not contain "citrus-based" solvents



TECHNICAL SPECIFICATIONS

| PROPERTIES | TEST METHOD | VALUE |
|--------------------------------------|-----------------------------------------|---------------------------------------------|
| Appearance | – | Clear liquid |
| Odor | – | Mild solvent odor |
| Flash Point | ASTM D93 | 147F (PMCC) |
| Evaporation Rate (n-Butyl Acetate=1) | ASTM D1901 | 0.10 |
| Vapor Pressure @ 77F | – | <3mm Hg |
| Vapor Density (Air=1) | – | <1 |
| Specific Gravity | ASTM D287 | 0.793 |
| Boiling Range | ASTM D86 | 367° - 400°F |
| Pour Point | ASTM D97 | -60°F |
| Solubility in Water | – | 1.01% weight (negligible) |
| % Non-volatile Residue | ASTM D2369 | <100 ppm residue |
| | (modified test: 10 gram sample @ 158°F) | |
| Dielectric Strength | ASTM D877 | >50,000 volts |
| Corrosion Test | 24 hours immersion @ 75°F and 122°F | Non-corrosive to steel, copper and aluminum |
| Stress Cracking | ASTM D1693 (14 days @122°F) | No cracking seen in LLDPE< LDPE, HDPE |

ORDER REFERENCE

| DESCRIPTION | SHIPPING WEIGHT (LBS) | PART # |
|-------------------------------------------|-----------------------|----------|
| C-200 Multipurpose Cleaner - (12) 1 Quart | 20.7 | 2000011 |
| C-200 Multipurpose Cleaner - 5 Gal Pail | 33 | 20097948 |

NOTE: Although C-200 Multipurpose Cleaner is formulated to have a low level of toxicity, prolonged contact may cause skin drying in some individuals. To minimize contact, gloves and appropriate work clothing should be worn. C-200 is easily washed off the skin with soap and water. If C-200 Multipurpose Cleanser gets into the eyes, flush with water. Medical attention should be obtained immediately if taken internally. Do not induce vomiting. Use caution when cleaning equipment around sources of ignition. Keep away from heat, sparks, and open flames. Consult C-200 Multipurpose Cleaner Material Safety Data Sheet for additional information.