

STANDARD ACCESSORIES

REDI-LOCK

- ▶ Available in sizes 2" through 6"
- ▶ Ideal for joining lengths of HDPE sticks, but can also be used with continuous length, reeled products
- ▶ Stainless steel band clamps (hand tightened using a 5/16" nut driver) with self-locking ring
- ▶ UV stabilized
- ▶ High strength molded plastic body ideal for buried duct applications
- ▶ Air- and water-tight
- ▶ NOTE: If coupling HDPE to PVC, use Shur-lock II coupler



ORDER REFERENCE

| DESCRIPTION | NOM OD | PULL-OUT STRENGTH (LBS) | MAX PRESSURE (PSI) | CARTON QTY | PART # |
|------------------|--------|-------------------------|--------------------|------------|----------|
| 2" Redi-Lock | 2.375" | 700 | 70 | 10 | 20005477 |
| 2 1/2" Redi-Lock | 2.875" | 750 | 55 | 6 | 20005478 |
| 3" Redi-Lock | 3.500" | 950 | 40 | 6 | 20005479 |
| 4" Redi-Lock | 4.500" | 950 | 40 | 4 | 20005480 |
| 5" Redi-Lock | 5.563" | 1,000 | 40 | 2 | 20005481 |
| 6" Redi-Lock | 6.625" | 1,000 | 15 | 2 | 20005482 |



An Orbia Connectivity Solutions business.

+1 800 847 7661
WWW.DURALINE.COM

TL9000

