

SAFETY DATA SHEET

1. Identification

Product identifier	HydraLube F-100i Summer
Other means of identification	None.
Recommended use	Lubricant.
Recommended restrictions	Uses other than the recommended use.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer	Connectivity Solutions (Dura-Line) 11400 Parkside Drive, Suite 300 Knoxville, TN, USA 37934
Telephone	1-800-847-7661
Emergency Telephone Number	1 866-519-4752 (US, Canada)
Access code	58811

2. Hazard(s) identification

Hazards of the product as supplied

Physical hazards	Not classified.	
Health hazards	Sensitization, skin	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 3
	Hazardous to the aquatic environment, long-term hazard	Category 3
OSHA defined hazards	Not classified.	
Other hazards		
Hazard(s) not otherwise classified (HNOC)	No additional hazards are known to be associated with the expected conditions of use at the time of publication. This document does not address hazards that may arise from uses not reasonably anticipated by the manufacturer.	

Label elements



Signal word	Warning
Hazard statement	May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.
Precautionary statement	
Prevention	Avoid breathing mist/vapors. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves.
Response	If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
Storage	Not assigned.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Potassium hydroxide	1310-58-3	0.33444
5-Chloro-2-methyl-2,3-dihydroisothiazol-3-one and 2-Methyl-2,3-dihydroisothiazol-3-one (3:1)	55965-84-9	< 0.005
Benzene	71-43-2	0.00085

Composition comments All concentrations are in percent by weight.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Water runoff can cause environmental damage.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Prevent product from entering drains. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Absorb spillage with suitable absorbent material. Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. Persons susceptible to allergic reactions should not handle this product.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Components	Type	Value
Benzene (CAS 71-43-2)	STEL	5 ppm
	TWA	1 ppm

US. OSHA Table Z-2 Permissible Exposure Limits (PEL) (29 CFR 1910.1000)

Components	Type	Value
Benzene (CAS 71-43-2)	Ceiling	25 ppm
	TWA	10 ppm

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value
Benzene (CAS 71-43-2)	TWA	0.02 ppm
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m3

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
Benzene (CAS 71-43-2)	IDLH	500 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Benzene (CAS 71-43-2)	STEL	1 ppm
	TWA	0.1 ppm
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m3

Biological limit values

ACGIH

Components	Value	Determinant	Specimen	Sampling Time
Benzene (CAS 71-43-2)	500 µg/g	t,t-Muconic acid	Creatinine in urine	*

ACGIH Biological Exposure Indices (BEI)

Components	Value	Determinant	Specimen	Sampling Time
Benzene (CAS 71-43-2)	25 µg/g	S-Phenylmercapturic acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Benzene (CAS 71-43-2) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Benzene (CAS 71-43-2) Danger of cutaneous absorption

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection	Chemical goggles and face shield are recommended.
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
Skin protection	
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134. Appropriate respirator selection should be made by a qualified professional.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Physical state	Liquid.
Form	Liquid.
Color	White or milk-white.
Odor	Mild.
Melting point/freezing point	Property has not been measured.
Boiling point or initial boiling point and boiling range	212 °F (100 °C)
Flammability	Non flammable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	The product is not flammable.
Explosive limit - upper (%)	The product is not flammable.
Flash point	Not flammable or combustible.
Auto-ignition temperature	Property has not been measured.
Decomposition temperature	Not applicable as the product is not unstable.
pH	> 7 - < 8
pH concentration	Property has not been measured.
Kinematic viscosity	Property has not been measured.
Kinematic viscosity temp	Property has not been measured.
Solubility	
Solubility (water)	Soluble (10- 99%)
Partition coefficient (n-octanol/water)	Property has not been measured.
Vapor pressure	Property has not been measured.
Vapor pressure temp.	Property has not been measured.
Density and/or relative density	
Density	Property has not been measured.
Relative density	1.01
Relative density temperature	Property has not been measured.
Vapor density	Property has not been measured.
Vapor density temp.	Property has not been measured.

Particle characteristics Not applicable, material is a liquid.

Other information

Dynamic viscosity Property has not been measured.

Dynamic viscosity temp Property has not been measured.

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact May cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity

Product	Species	Test Results
HydraLube F-100i Summer (CAS Mixture)		
<u>Acute</u>		
Dermal		
ATEmix		4029000 mg/kg bw
Oral		
ATEmix		94430 mg/kg bw

Components	Species	Test Results
Benzene (CAS 71-43-2)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 8260 mg/kg
Inhalation		
<i>Vapor</i>		
LC50	Rat	44.66 mg/l, 4 Hours
Oral		
LD50	Rat	810 mg/kg

Potassium hydroxide (CAS 1310-58-3)

<u>Acute</u>		
Oral		
LD50	Rat	333 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Not classifiable as to carcinogenicity to humans.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Benzene (CAS 71-43-2)	1 Carcinogenic to humans.
NTP Report on Carcinogens	
Benzene (CAS 71-43-2)	Known To Be Human Carcinogen.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)	
Benzene (CAS 71-43-2)	Cancer
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity	Harmful to aquatic life with long lasting effects.		
Components	Species		Test Results
Benzene (CAS 71-43-2)			
Aquatic			
Acute			
Algae	EC50	Pseudokirchneriella subcapitata	29 mg/l, 72 Hours
Crustacea	EC50	Daphnia magna	10 mg/l, 48 hours
Fish	LC50	Oncorhynchus mykiss	5.3 mg/l, 96 hours
Chronic			
Algae	NOEC	Selenastrum capricornutum	41 mg/l, 8 days
Crustacea	NOEC	Ceriodaphnia dubia	3 mg/l, 7 days
Fish	NOEC	Pimephales promelas	0.8 mg/l, 32 days
Potassium hydroxide (CAS 1310-58-3)			
Aquatic			
Fish	LC50	Western mosquitofish (Gambusia affinis)	80 mg/l, 96 Hours
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential			
Partition coefficient n-octanol / water (log Kow)			
Benzene (CAS 71-43-2)	2.13		
Mobility in soil	No data available.		
Other adverse effects	No data available.		

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
------------------------------	--

Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to IMO instruments Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA) One or more components of the mixture are not on the TSCA 8(b) inventory or are designated "inactive".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Benzene (CAS 71-43-2)

Potassium hydroxide (CAS 1310-58-3)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Benzene (CAS 71-43-2)

Cancer
Central nervous system
Blood
Aspiration
Skin
Eye
respiratory tract irritation
Flammability

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Respiratory or skin sensitization

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Benzene (CAS 71-43-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Benzene (CAS 71-43-2)

US. Massachusetts RTK - Substance List

Benzene (CAS 71-43-2)

Potassium hydroxide (CAS 1310-58-3)

US. New Jersey Worker and Community Right-to-Know Act

Benzene (CAS 71-43-2)

Potassium hydroxide (CAS 1310-58-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Benzene (CAS 71-43-2)

Potassium hydroxide (CAS 1310-58-3)

US, Rhode Island RTK

Benzene (CAS 71-43-2)

Potassium hydroxide (CAS 1310-58-3)

California Proposition 65



WARNING: This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2)

Listed: February 27, 1987

California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2)

Listed: December 26, 1997

California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2)

Listed: December 26, 1997

16. Other information, including date of preparation or last revision

Issue date 22-June-2026

Revision date -

Version # 01

HMIS® ratings

Health:	2
Flammability:	0
Physical hazard:	0

Disclaimer Dura-Line cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.